



Point Vision PV6SYPTZB Combination of PTZ & Fixed Bullet Network Cameras

This platform allows the user to view a wide area with the two fixed bullet cameras while retaining the ability to pan, tilt and zoom (28x) on the subject area without losing sight of the entire field of view.

- Modular & Portable
- Web-based User Interface
- Integrated Climate Control
- Intel PC w/Windows 10
- Cellular/WiFi/Wireless
- 802.3 AT Internal/External POE Power Ports
- 12VDC, 24 VDC, 56 VDC Available to Power Accessories
- SNMP Communications

The Point Vision (PV) product line is the world's smartest IoT Video Surveillance Platform. The PV video cameras are internally networked with a cellular router and Windows based PC that capture, store, analyze video and stream (locally) at the edge. Each device is configured with two onboard computers, POE switch, router with embedded 4G LTE modem, Wi-Fi, wireless, and PTZ or fixed cameras. Video can be stored and streamed anywhere there is a cellular and/or hard-wire Ethernet connection. Proprietary Web-based GUI connects the user remotely to each device for configuration and power management.



PV6SYPTZB DATASHEET

Environmental Specifications

Operating Temperature	-40 - 140°C
Weather Resistance	IP66

Input Power

Input Voltage Range	100-240 VAC
Input AC Frequency	50/60 Hz
Max Power Consumption	7.5A at 120V (900 Watts)
Typical Power Consumption	1.3A at 120V (177 Watts)

Physical Specifications

Weight	12.4Kg (27.3 lbs)
Dimensions (H x W x D)	508 x 340 x 458 (20" x 13.375" x 18")

Network Specifications

Ethernet Switch	4 Port 10/100Mb
-----------------	-----------------

Climate Control

Peltier Based Cooling System	
------------------------------	--

Included Devices

Included Devices	Model Number
Intel NUC	NUC6i5SYK
2 HikVision Bullet Cameras	DS-2CD2032-I
Sony PTZ Camera	SNC-EP550
Cradlepoint Cellular Router	IBR600
Ubiquiti 5 Port ToughSwitch	TS-POE-5

HikVision Cameras

Model	DS-2CD2032-I
Image Sensor	1/3" progressive scan CMOS
Number of effective pixels	3 Megapixel
Minimum Illumination	0.07 lux @F1.2, AGC ON 0 lux with IR
Lens Type	4mm @F2.0, angle of view: 75.8°
ONVIF Compliance	ONVIF® Profile S and ONVIF® Profile G
Max Resolution	2048 x 1536
Max Framerate	50Hz: 12.5fps (2048 x 1536), 25fps (1920 x 1080), 25fps (1280 x 720) 60Hz: 15fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)

Sony Camera

Model	SNC-EP550
Image Sensor	1/4-type Exmor CMOS
Number of effective pixels	Approx. 1.43 Megapixel
Minimum Illumination	Color: 2.0lx
Electronic Shutter Speed	1/1 to 1/10,000 s
Lens Type	Auto-focus Zoom Lens
Zoom Ratio	Optical zoom 28x, Digital zoom 12x
ONVIF Compliance	Yes (Ver. 1.02)
Max Resolution	1280x720
Max Framerate	30 fps

Intel NUC

Model	NUC6i5SYK
Processor	i5-6260U
Processor Cores	2
Processor Speed	1.8GHz turbo boost to 2.9GHz
Memory	up to 32GB DDR4
Storage	up to 2TB M.2 SSD, or 2.5" Hard Drive
Graphics	Intel Iris Graphics 540
Operating System	Windows 10 IOT

Cradlepoint Router

Model	IBR600
Cellular	Integrated 3G/4G Modem
Ethernet	2 LAN/WAN Ports
WiFi	Wireless 2x2 MIMO "N" (802.11 b/g/n)
WiFi Security	WEP, WPA, WPA2, WPA2 Enterprise with AES encryption
Security	Zone-based Firewall, SPI, and NAT
VPN	IPsec VPN (up to 5 concurrent sessions)

Ubiquiti ToughSwitch

Model	TS-POE-5
LAN Ports	5 10/100/1000Mb Ports (2 Free with all Internal devices hooked up)
Management Port	1 10/100Mb Port
POE	Configurable 24V Passive POE on LAN Ports